

Fast charging station for electric vehicles

SPEEDY CHARGER SKY 200 R55

Electric cars are no longer the future, but became the presence and charging from the socket is the fuel of tomorrow.

Electric vehicles are considered to be one of the solutions with respect to the environment, because produce no emissions. And we have the solution for customers and owners of electric vehicles, electric bikes and electric scooters. Introducing modern, stylish Fast-charging station, yet unique of its kind, for charging all kind of battery vehicles.

Charging is easy enough. Use the charging cable to simply connect the vehicle to the charging station. You can fully or partially recharge vehicle as needed. Recharge depends on the vehicle and the type of battery.

Fast charging will be comparable to the fuelling from the petrol station. An advantage is that it can be installed in any environment. It is suitable for fleets, owner of petrol stations, shopping centers, etc.

Specification

- Fast charging
- Elegant design
- Modular system
- Integrated communication
- Light indication
- Insulated power module; customer is protected; electrical safety
- AC and DC charging modes
- Intelligent charging
- **IP 44 or IP 54 protection**

For operator:

- Integrated and intelligent solution for electric vehicle charging
- Modification upon request
- Installation and service
- Remote system control
- Error reports and service request via SMS and e-mail
- Optional security camera

For customer:

- Fast and safe charging
- Simple, efficient and easily controllable system
- Maximal total safety for customer and electric vehicle
- Intuitive and easily usable graphical user interface
- Easily accessible
- Allows charging of all electric vehicles including cars, bikes and scooters
- Maximum charging cost selection



TECHNICAL PARAMETERS

INPUT

Voltage	3x 230/400 V ±10 %
Frequency	50/60 Hz
Maximal current	320 A
Maximal power	220 kVA
PF	For maximal power > 0,95

DC OUTPUT

Maximal power	> 200 kW
Maximal current	2 x 250 A
Output voltage	50 - 500 V

SAFETY AND ELECTRIC SPECIFICATION

Efficiency	> 95 %
Short circuit protection	Yes
Overvoltage protection	Yes
El. isolated AC/DC Output	Yes
Total stop button	Yes
Safety	Isolation transformer Control wire
Charging protocol	CCS (Combo 2) CHAdeMO
AC sockets	MENNEKES 400 V, 32 A

SPECIFICATION

Dimensions (H x W x D)	1800 x 1050 x 1000 mm
Weight	580 kg
Protection	IP44 or IP54
Cooling medium	Air

ENVIROMENTAL VARIABLES

Temperature	-25 °C to +40 °C
Maximal humidity	90 %, without condensation

CERTIFICATION

General certifications	Yes
CHAdeMO + Cobmo2	Yes

USER INTERFACE

Screen	10.2" Graphic touch display
Button	Stop button
Charging information	Battery status Elapsed and remaining time Actual voltage and current Transferred energy Total cost
Interactive menu	Language selection Maximal charging cost Receipt printing (optional)

COMMUNICATION

RFID (optional)	ISO 14443 Type A
Standard interfaces	RS-232, RS-485, CAN
Ethernet (optional)	GSM/GPRS or LAN

PAYMENT SYSTEM (OPTIONAL)

Credit cards	VISA Master Card
Contactless credit cards	Yes
Receipt	Yes

SECURITY (OPTIONAL)

Security	CMOS camera
Alarm	Sound and light alarm

NEXT TYPES

SP. CHARGER SKY 100 R55	DC 100 kW, max. 250 A
SP. CHARGER SKY 50 R55	DC 50 kW, max. 125 A

We can modify charging station upon customer request.

SKYBERGTECH s.r.o.

U Mototechny 107
251 62 Tehovec
Identification number: 25092235
TAX ID: CZ25092235
E-mail: obchod@skybergtech.com
info@skybergtech.com
Web: <http://www.skybergtech.com>
Tel.: +420 323 660 013
+420 323 605 511